

Pneu-Dart X-CALIBER Suggested Pressure Settings for Transmitter RDDs

1cc Transmitter RDD

YARDS	New Style	Hold	Old Style	Hold
5 =	3.5 bar	0	4 bar	0
10 =	4.5 bar	0	5 bar	0
15 =	6.5 bar	0	6.5 bar	0
20 =	8 bar	0	8 bar	0
25 =	9 bar	0	10 bar	0
30 =	11 bar	0	13.5 bar	0
35 =	13.5 bar	0	14.5 bar	0
40 =	15 bar	0	16.5 bar	0
45 =	18 bar	0	18.5 bar	0

2cc Transmitter RDD

YARDS	New Style	Hold	Old Style	Hold
5 =	4 bar	0	4 bar	0
10 =	5 bar	0	5.5 bar	0
15 =	6.5 bar	+2	7 bar	0
20 =	8 bar	0	9 bar	0
25 =	9.5 bar	0	11.5 bar	0
30 =	13 bar	0	13.5 bar	0
35 =	15 bar	0	15.5 bar	0
40 =	17.5 bar	0	17.5 bar	0
45 =	20 bar	+6	19 bar	0

3cc Transmitter RDD

YARDS	New Style	Hold	Old Style	Hold
5 =	4 bar	0	4.5 bar	0
10 =	5 bar	0	5.5 bar	0
15 =	7 bar	0	7 bar	0
20 =	9 bar	0	9.5 bar	0
25 =	10 bar	0	12 bar	0
30 =	11.5 bar	0	14.5 bar	0
35 =	12.5 bar	0	16 bar	0
40 =	15 bar	0	18.5 bar	0
45 =	19 bar	+6	20 bar	+6

Please note: This chart is merely a guideline. We encourage all customers to independently construct a trajectory chart with their own projector prior to delivering a RDD at an animal. Projectors sold prior to 3/02 are not compatible, please return your projector to receive free up-grade. (Shipping N.I.)

(+) = implies hold above intended point of impact
 (-) = implies hold below intended point of impact
 NR = not recommended

