

# Pneu-Dart X-2 Suggested Pressure Settings for 1/2cc – 3cc Dart Capacities

Distance	1/2 cc	Reticle Position	1 cc	Reticle Position	1 1/2 cc	Reticle Position	2cc	Reticle Position	3cc
5 yds =	2.5 BAR	(+) 2"	3.0 BAR	(+) 1"	3.0 BAR	(+) 4"	3.0 BAR	(+) 1"	4.0 BAR
10 yds =	4.0 BAR	(-) 1"	4.0 BAR	(+) 1"	4.5 BAR	(+) 1"	5.0 BAR	0	6.0 BAR
15 yds =	5.0 BAR	0"	5.5 BAR	(+) 1"	6.5 BAR	(-) 3/4"	6.0 BAR	0	7.0 BAR
20 yds =	7.5 BAR	(+) 2"	7.5 BAR	(+) 4"	8.0 BAR	0	9.5 BAR	(+) 1"	10 BAR
25 yds =	9.0 BAR	(-) 2"	8.5 BAR	0"	10.0 BAR	0	NR	NR	NR

**Please note:** This chart is a general guideline when using fully loaded Pneu-Dart darts.  
Intended impact velocities may require alternate settings and/or altered points of aim.

(+) = implies hold above intended point of impact  
(-) = implies hold below intended point of impact  
NR = not recommended

BAR	PSI	BAR	PSI	BAR	PSI	BAR	PSI	BAR	PSI
4.1	60	5.2	75	6.2	90	7.6	110	9.7	140
4.5	65	5.5	80	6.6	95	8.3	120	10.3	150
4.8	70	5.9	85	6.9	100	9.0	130	11.7	170

